Component - Plastics

File Number: E54699

ARKEMA INC
900 1ST AVE
KING OF PRUSSIA, PA 19406-1308 United States

Kynar 720(f1)

Polyvinylidene Fluoride (PVDF), pellets

(f1) - Suitable for outdoor use with respect to exposure to Ultraviolet Light, Water Exposure and Immersion in accordance with UL 746C.

Flammability	Value	Test Method
Flame Rating (1.5 mm, NC)	V-0	UL 94 IEC 60695-11-10, -20
Thermal	**Value**	**Test Method**
RTI Elec (1.5 mm)	150 °C	UL 746
RTI Imp (1.5 mm)	150 °C	UL 746
RTI Str (1.5 mm)	150 °C	UL 746
Physical	**Value**	**Test Method**
Outdoor Suitability	f1	UL 746C

Form Number: E54699-244848

UL and the UL logo are trademarks of UL LLC Copyright © 2020 All Rights Reserved. | www.ul.com

Report Date: 2012-09-10
Last Revised: 2019-07-08

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.