

SECTION X-X




1:1

MOUNTING HOLE:  $\phi 8.0 - 8.1$  mm  
 PANEL THICKNESS: 0.8-1.5 mm

**APPROVED - UNCONTROLLED**

UNLESS OTHERWISE STATED

ALL DIMENSIONS IN mm		DO NOT SCALE	
LINEAR TOLERANCE		THIRD ANGLE PROJECTION	
SIZE	(0) (0.0) (0.00)	 ANGULAR TOLERANCE $\pm 0.5$ DEGREES UNSPECIFIED RADII 0.25mm DRAFT ANGLE 0.5 DEGREES DIMENSIONS IN BRACKETS [ ] ARE IN INCHES FOR REFERENCE ONLY	
0-10mm	$\pm 0.5 \pm 0.15 \pm 0.10$		
>10-30	$\pm 0.5 \pm 0.20 \pm 0.15$		
>30-50	$\pm 0.5 \pm 0.30 \pm 0.20$		
>50-100	$\pm 0.8 \pm 0.50 \pm 0.25$		
>100-200	$\pm 1.5 \pm 0.80 \pm 0.40$		
>200-300	$\pm 2.0 \pm 1.20 \pm 0.80$		
>300-500	$\pm 3.0 \pm 2.00 \pm 1.00$		
>500	$\pm 5.0 \pm 3.00 \pm 1.50$		

ORG. SCALE: 2:1      CREATE DATE: 11/09/2018

MATERIAL: FOOT: TPV, PIN: PP

Part ID: 1092613      Project: P100095-3

TITLE: SOFT FAST FOOT

DWG. No.

SFF-023

SHEET  
1 of 1  
ISSUE  
1