Component - Plastics

File Number: E170540

DOMO ENGINEERING PLASTICS EUROPE SPA
VIA LINFANO 18
ARCO, TN 38062 Italy

Technyl: C 202, C 216F, C 216FC, C 216FFC, C 216, 6FC, 6, 6 101, S 6

Polyamide 6 (PA6), pellets

NOTE - - Materials designated "Technyl" may be prefixed by the letters "TY". Optional color name (in letters) followed by 1 to 10 alphanumeric code. Materials with codes ending with letter "D" alone are not UL Recognized

Flammability	Value	Test Method
Flame Rating (0.8 mm, ALL)	V-2	UL 94 IEC 60695-11-10, -20
Thermal	**Value**	**Test Method**
RTI Elec (0.8 mm)	65.0 °C	UL 746B
RTI Imp (0.8 mm)	65.0 °C	UL 746B
RTI Str (0.8 mm)	65.0 °C	UL 746B

Form Number: E170540-225449

UL LLC Copyright ©2022. All rights reserved. | www.ul.com

Report Date: 10/20/1995
Last Revised: 2/4/2022 6:07:22 AM

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.