



Note: Threaded parts must accept 2A GO gage.
Per current fastener industry practice,
if form, fit, and function are achieved,
parts may accept 2A NO GO.

ACTUAL SIZE

FOR CUSTOMER APPROVAL ONLY				REV	BY	DATE	COMMENT	DIMENSIONS ARE IN INCHES TOLERANCES FRACTIONAL ± TWO PLACE DECIMAL ± 0.03 THREE PLACE DECIMAL ± 0.010 UNLESS OTHERWISE NOTED		DRAWN	VRR	 INNOVATIVE COMPONENTS		
NAME:				0	JBA	08/13/13	RELEASE DATE			APPROVED	LQR	PART NAME 1.75" 3-Prong Knob 10-24 X 1/2" Steel, Zinc		
				1	VRR	11/6/2013	Added thread specs			DATE	11-6-2013			
TITLE:							COMMENTS							
DATE:								KNOB MATERIAL Polypropylene, Black	INSERT MATERIAL Steel		PART NUMBER KNO405003P4--21 DRAWING NUMBER 11-5-13 R1			
SIGNATURE:				PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INNOVATIVE COMPONENTS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF INNOVATIVE COMPONENTS IS PROHIBITED.				KNOB FINISH Textured		INSERT FINISH Zinc				
								INSERT PART NUMBER MS041250RS---21				SCALE 1:1		SHEET 1 OF 1



PLASTIC KNOBS / CONTROL KNOBS / HANDLES / QUICK RELEASE PINS & BALL LOCK PINS
SPRING LOADED PINS & PLUNGERS / WIRE ROPE LANYARDS / THREAD IDENTIFIERS